

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT-COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
1 July 2004 (01.07.2004)


PCT

(10) International Publication Number  
WO 2004/055359 A1

- (51) International Patent Classification<sup>7</sup>: F02M 57/02, 59/10
- (21) International Application Number: PCT/GB2003/005554
- (22) International Filing Date: 18 December 2003 (18.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0229487.4 18 December 2002 (18.12.2002) GB
- (71) Applicant (for all designated States except US): DELPHI TECHNOLOGIES, INC. [US/US]; P.O. Box 5052, Troy, MI 48007 (US).
- (72) Inventors; and  
(75) Inventors/Applicants (for US only): HARCOMBE, Anthony, Thomas [GB/GB]; 1 Warren Avenue, Richmond, Surrey TW10 5DZ (GB). WILLIAMS, Anthony, John [GB/GB]; 39 Sussex Avenue, Isleworth, Middlesex TW7 6LJ (GB).
- (74) Agents: KELTIE, David, Arthur et al.; David Keltie Associates, Fleet Place House, 2 Fleet Place, London EC4M 7ET (GB).
- (81) Designated States (national): JP, US.
- (84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- Published:  
— with international search report

[Continued on next page]

(54) Title: CAM ARRANGEMENT AND FUEL PUMP ARRANGEMENT INCORPORATING A CAM ARRANGEMENT



(57) **Abstract:** A cam arrangement for use with a high pressure fuel pump arrangement for delivering fuel to an associated engine, the cam arrangement including at least two cams (28) that are mounted, in use, upon an engine camshaft and each of which is arranged to drive a respective pumping plunger (16) of the fuel pump arrangement, wherein each plunger is driven to perform a pumping stroke, against return biasing means (32), during which fuel within a pump chamber (22) associated with each plunger is pressurised, and whereby said return biasing means (32) effects a plunger return stroke, and wherein each cam (28) is oriented relative to the or each other cam and has a surface (50) shaped such that the associated plunger return stroke is interrupted to define at least one step of plunger movement that is substantially synchronous with the pumping stroke of another of the plungers (16) of the pump, thereby to reduce negative torque loading of the camshaft.

WO 2004/055359 A1